

RAW MATERIAL DATA SHEET

MHPS FILTER

COMPOSITION

OPEN-CELL POLYURETHANE FOAM, COATED WITH ACTIVATED COAL POWDER

PHYSICAL CHARACTERISTICS

MAXIMUM COAL SIZE	0,65 x 50 μ m.
THICKNESS	10 mm (\pm 0,5)
WEIGHT PER LAYER	650 \pm 50 GR/Mq.
ACTIVE COAL WEIGHT	200 \pm 20 GR/Mq.
N-BUTANE ADSORPTION (MG/CM ²) (80PPM N-BUTAN, V = 0,17 M/S 23°C 50% UMID. REL.)	> 0,15
LOAD LOSSES AT 0,8 M/S	\leq 30 PA
FLAMMABILITY CLASS (DIN 53438 PART 3)	F1

THE INFORMATION IN THESE TECHNICAL SHEET ARE BASED ON ANALYSIS OF MATERIAL SUPPLIED SO FAR.
THEY ARE NOT BINDING.

RESETT ENGINEERING SRL

SEDE LEGALE VIA BALBO, 35 60044 FABRIANO AN
STAB./ AMM. VIA PIANI DI MARISCHIO 38 60044 FABRIANO AN
TEL. 0039 0732 73551 FAX 0039 0732 73473
P. IVA 02220740423 CAP. soc. € 10.000,00