

PRE TECHNICAL RAW MATERIAL DATA SHEET

ULTRASORB -11

MEDIA COMPISITION	RETICULATED POLYURETHANE FOAM, COATED WITH ACTIVATED SHERICAL CARBON
WEIGHT PER UNIT AREA (G/M ²) ACCORDING TO DIN EN 12127	2200 ± 300
CONTENT OF ACTIVATED CARBON (G/M)	1700 ± 200
THICKNESS (MM) LG 050	11,0 ± 0,5
DIFFERENT PRESSURE (PA) AT 0,8 M/S	<40
N-BUTANE ADSORPTION (MG /CM) (80 PPM N-BUTAN, V = 0,17 M/S, 23°C, 50% REL. HUMID.)	>4
FLAMMABILITY (ERIGE) DIN 53438, PART2	CLASS K1
FLAMMABILITY (AREA) DIN 53438, PART 1	CLASS F1

THIS INFORMATION HAS BEEN GATHERED FROM STANDARD REFERENCE MATERIALS THAT IS ASSUMED TO BE ACCURATED AND RELIABLE. COMELT S.P.A. DOES NOT ASSUME ANY LIABILITY AND RISK THAT MAY ARISE FROM THE USE OF THIS PRODUCT, INCLUDED BUT NOT LIMITED TO FITNESS FOR A PARTICULAR PURPOSE OR APPLICATION.

RESETT ENGINEERING SRL

SEDE LEGALE VIA BALBO, 35 60044 FABRIANO AN
STAB./ AMM. VIA PIANI DI MARISCHIO 38 60044 FABRIANO AN
TEL. 0039 0732 73551 FAX 0039 0732 73473
P. IVA 02220740423 CAP. soc. € 10.000,00